

SERIES 2127

Light weight, high intensity, multi-purpose, hand held light delivers up to 70,000 candlepower direct to the task with negligible glare or shadow.

Ideal for inspection, installation, assembly, service and repair work -- indoors or outdoors, above or below ground, in wet or damp locations, as well as dry. No exposed metal.

A versatile light having wide application in many industries demanding reliable, safe and intense glare-free illumination.

Only 6 volts at your hand maximizes safety and satisfies OSHA requirements for "portable lighting used in moist and/or other hazardous locations." [1926.401j (4)]



FEATURES

- One piece molded housing.
- Bulb protected against breakage.
- Totally enclosed transformer.
- No exposed metal parts.
- Neoprene seals protect against moisture and guard against spark hazards.
- Light weight -- built to take abuse.
- Low voltage at the hand.

SPECIFICATIONS

HOUSING

Molded Polypropylene

LENS

Molded Lexan[®] (or tempered glass).

BULB

55,000 candlepower, 30 watt, 6 volt sealed beam #4515, H7616, 37.5 watt, 112.8V, 70,000 candlepower.

SWITCH

On-off push button protected by neoprene cover.

TRANSFORMER

Isolated winding, shielded and grounded, epoxy encapsulated and totally covered in neoprene.

WEIGHT

Total include. transformer -- 8 1/2 lbs.;
Hand piece only -- 1 lb., 8 oz.

DIMENSIONS

Head -- 3" diameter.
Handle -- 1.5" diameter, 9" long.

MODEL NO.	DESCRIPTION	SHIP WT/LBS
2127-1	55,000 candlepower- 120V/6V transformer- 30 watts CORD 50 ft. 16/2 SJO Secondary and 6 ft. 16/3 primary. With plug.	9
2127-803	55,000 candle power - 120V/6V transformer - 30 watts CORD 36 ft. 16/2 SJO Secondary and 6 ft. 18/3 50 PRI. No plug. For use in hazardous locations: Class I, Div. 2, Group D Class II, Div. 1, Group G	9
2127-110V	55,000 candle power - 120V/6V transformer - 30 watts CORD 36 ft. 16/2 SJO Secondary and 6 ft. 18/3 50 PRI. with plug.	9
2127-501	55,000 candlepower - 220V/6V transformer - 30 watts CORD 30 ft. 16/2 SJO Secondary and 6 ft. 18/3 SJO PRI. No plug.	9
2127-511	70,000 candle power- 120V/12V transformer - 37.5 watts (Halogen bulb) CORD 30 ft. 16/2 SJO Secondary and 6ft. 18/3 PRI. With plug.	9